

LION



RX2-A/RX3-A

860-Lion receiver RX2-A/RX3-A	
Article number:	860RX-MD-10B (RX2-A) and 860RX-MX-15B/24B (RX3-A)
Application areas:	Cranes, EOT cranes, towing and recovery vehicles, chrushers, dump bodies, load changers, agriculture machines
Frequency:	433 - 434 MHz (69 channels)
Mod.Type:	Narrow band FM-modulation
Coding:	Digital pulse code
Code comb.:	65.536
Relay output:	RX3-A: 15 or 24+2 for stopfunction RX2-A: 10+2 for stopfunction Stop Relay; Potential free, close 8A AC I Function Relay; Potential free, open / close 16A AC I Simultaneous Momentary/Latching Interlocking functions
Radio type:	Double superheterodyne PLL syntesiser
Sensitivity:	-120 dBm (SINAD 12 db)
Antenna:	External
Power supply:	12/24 V AC/DC and 48/115/230 V AC
Weight:	RX2-A: 1.900g (4.19 lb) RX3-A: 2.100 g (4.63 lb)
Dimensions:	256 x 217 x 85 mm (10.08 x 8.54 x 3.35 in) incl. mounting brackets
Protection:	IP 65
Recommended transmitter:	860-Lion TX2-A and TX3-A

N.L. Tucker & Associates Pty Ltd
12B Pitt Way
Booragoon, WA 6154
P: 08 9330 7911
F: 08 9317 1544
sales@nltucker.com.au

N.L. Tucker & Associates Pty Ltd
50 Marni Street
Dandenong South, Victoria 3175
P: 03 9706 6691
F: 03 9706 6692
vicsales@nltucker.com.au