



T20/T60RX-01APL

Receiver Plug-in T20/T60RX-01APL:	
Application areas:	Doors, entrances, gates, a.o.
Frequency:	433,92 MHz
Mod. Type:	FSK
Coding:	Digital pulse code
Cod comb.:	59-049 and unique code 16.777.216 (System 460: 6.561)
Relay output:	1, Self-learning, 60 codes Potential free, close 8 A
Radio type:	Double superheterodyne
Sensitivity:	-100 dBm or better at 12 dB Sinad
Antenna:	External
Power supply:	12-24V AC / DC
Power consumption:	12-24V AC; 40-80 mA 12-24V DC; 35-70 mA
Temperature:	- 30° to + 70° C
Dimensions:	70 x 58 x 40 mm
Protection:	IP 20
Recommended transmitter:	All transmitters system T20/T60 with 433,92 MHz (fully compatible with system 460)

N.L. Tucker & Associates Pty Ltd
12B Pitt Way
Booragoon, WA 6154
P: 08 9330 7911
F: 08 9317 1544
sales@nltucker.com.au

N.L. Tucker & Associates Pty Ltd
50 Marni Street
Dandenong South, Victoria 3175
P: 03 9706 6691
F: 03 9706 6692
vicsales@nltucker.com.au