



T20RX-02AKL/AKM

Receiver T20RX-02AKL:	
Application areas:	Doors, entrances, gates a.o.
Frequency:	AKL receiver: 433,92 MHz AKM receiver: 869,85 MHz
Mod. Type:	FSK
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Relay output:	2 relay outputs, stores 15 codes on each relay, possibility to program; momentary / latching function on all relays
Radio type:	Double superheterodyne
Sensitivity:	- 100 dBm or better at 12 dB Sinad
Antenna:	External
Power supply:	12-24V AC / DC
Power consumption:	12-24V AC; 40-80 mA 12 - 24V DC; 35-70 mA
Temperature:	- 30° C to +70° C
Dimensions:	54 x 96 x 37 mm
Protection:	IP 54
Recommended transmitter:	AKL receiver: all transmitters system T20 with 433,92 MHz AKM receiver: all transmitters system T20 with 869,85 MHz

N.L. Tucker & Associates Pty Ltd
12B Pitt Way
Booragoon, WA 6154
P: 08 9330 7911
F: 08 9317 1544
sales@nltucker.com.au

N.L. Tucker & Associates Pty Ltd
50 Marni Street
Dandenong South, Victoria 3175
P: 03 9706 6691
F: 03 9706 6692
vicsales@nltucker.com.au