



T20RX-03ASx

Standard Receiver T20RX-03ASL/ASM:	
Application areas:	Doors, entrances, gates, winches, pumps, lighting, conveyor belts, hydraulics, a.o.
Frequency:	ASL receiver: 433,92 MHz ASM receiver: 869,85 MHz
Mod. Type:	FSK
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Relay output:	ASL receiver: 3 relay output; Stores 30 codes ASM receiver: 3 relay output; Stores 60 codes
Radio type:	Double superheterodyne
Sensitivity:	- 100 dBm or better at 12 dB Sinad
Antenna:	External
Power supply:	12 - 24V AC / DC
Power consumption:	12V DC; 50-300 mA 24V DC; 25-150 mA 24V AC; 20-120 mA
Temperature:	- 30° C to +70° C
Dimensions:	120 x 133 x 45 mm
Protection:	IP 65
Recommended transmitter:	ASL receiver: all transmitters system T20 with 433,92 MHz ASM receiver: all transmitters system T20 with 869,85 MHz

N.L. Tucker & Associates Pty Ltd
12B Pitt Way
Booragoon, WA 6154
P: 08 9330 7911
F: 08 9317 1544
sales@nltucker.com.au

N.L. Tucker & Associates Pty Ltd
50 Marni Street
Dandenong South, Victoria 3175
P: 03 9706 6691
F: 03 9706 6692
vicsales@nltucker.com.au