



T20TX-I5DMM



T20TX-I5SMM

<b>Maxi-M Transmitter T20TX-15DMM/T20TX-15SMM:</b>	
Application areas:	Doors, entrances, gates, winches, pumps, crushers, lighting, conveyor belts, hydraulics a.o.
Frequency:	869,85 MHz
Mod. Type:	FSK
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Functions:	<b>T20TX-I5DMM:</b> 3 functions, possibility to remote up to 1000 objects <b>T20TX-I5SMM:</b> 15 functions
Output:	10 mW (by 50 ohm)
Antenna:	Built-in
Power supply:	Exchangeable 9V battery type; 6F22 (battery change once a year with normal use)
Power consumption:	<b>T20TX-I5DMM:</b> Apr. 20 mA <b>T20TX-I5SMM:</b> Apr. 26 mA
Temperature:	-20° C to +55° C
Weight:	Apr. 155 g incl. battery
Dimensions:	143 x 62 x 28 mm
Protection:	IP 65
Recommended receiver:	All receivers system T20 with 869,85 MHz

**N.L. Tucker & Associates Pty Ltd**  
12B Pitt Way  
Booragoon, WA 6154  
P: 08 9330 7911  
F: 08 9317 1544  
sales@nltucker.com.au

**N.L. Tucker & Associates Pty Ltd**  
50 Marni Street  
Dandenong South, Victoria 3175  
P: 03 9706 6691  
F: 03 9706 6692  
vicsales@nltucker.com.au