



T20TX-01NKx



T20TX-02NKL



T20TX-03NKx

<b>Transmitter T20TX-0xNKL/NKM:</b>	
Application areas:	Doors, entrances, gates, winches, pumps, lighting, conveyor belts, hydraulics a.o.
Frequency:	<b>NKL transmitter:</b> 433,92 MHz <b>NKM transmitter:</b> 869,85 MHz
Mod. Type:	FSK
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Functions:	<b>NKL transmitter:</b> 1, 2 or 3 <b>NKM transmitter:</b> 1 or 3
Output:	Apr. 7 mW (by 50 ohm)
Antenna:	Built-in
Power supply:	exchangeable battery type: CR2032
Power consumption:	Apr. 25 mA
Temperature:	-20° C to +70° C
Weight:	Apr. 50 g incl. battery
Dimensions:	71 x 39 x 13 mm incl. clips
Protection:	IP 65
Recommended receiver:	<b>NKL transmitter:</b> all transmitters system T20 with 433,92 MHz <b>NKM transmitter:</b> all transmitters system T20 with 869,85 MHz

**N.L. Tucker & Associates Pty Ltd**  
12B Pitt Way  
Booragoon, WA 6154  
P: 08 9330 7911  
F: 08 9317 1544  
sales@nltucker.com.au

**N.L. Tucker & Associates Pty Ltd**  
50 Marni Street  
Dandenong South, Victoria 3175  
P: 03 9706 6691  
F: 03 9706 6692  
vicsales@nltucker.com.au