



T20TX-01SHx



T20TX-03SHx



T20TX-06SHx

Mini-H transmitter T20TX-0xSHL/SHM:	
Application areas:	Doors, entrances, gates, winches, pumps, lighting, conveyor belts, hydraulics a.o.
Frequency:	SHL transmitter: 433,92 MHz SHM transmitter: 869,85 MHz
Mod. Type:	FSK
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Functions:	1, 3 or 6
Output:	Apr. 7 mW
Antenna:	Built-in
Power supply:	Exchangeable 3 V battery type: CR2430 (battery change once a year with normal use)
Power consumption:	Apr. 18 mA
Temperature:	-15° C to +55° C
Weight:	Apr. 40 g incl. battery
Dimensions:	40 x 84 x 16 mm (with clip)
Protection:	IP 40
Recommended receiver:	SHL transmitter: all receivers system T20 with 433,92 MHz SHM transmitter: all receivers system T20 with 869,85 MHz

N.L. Tucker & Associates Pty Ltd
12B Pitt Way
Booragoon, WA 6154
P: 08 9330 7911
F: 08 9317 1544
sales@nltucker.com.au

N.L. Tucker & Associates Pty Ltd
50 Marni Street
Dandenong South, Victoria 3175
P: 03 9706 6691
F: 03 9706 6692
vicsales@nltucker.com.au