

# CHEETAH



T50-GSM I

<b>GSM unit T50-Cheetah GSM1</b>	
Article number:	T50RX-02AGSM
Area of application:	Doors, ports, gates, lighting, irrigation systems, alarm information, fault indication, etc
Supports the following cell networks:	EGSM 900, DCS 1800 and PCS 1900 Tripple Band
Control:	SMS, calling via a cell phone. A cell phone and a SIM card installed in the receiver are required to control the unit.
Relay outputs:	2 x 250V/8A NC/NO
Alarm inputs:	4, to send information to the cell phone via SMS
Antenna:	Internal
Operating voltage:	12/24V DC, 12V AC
Power consumption:	100-150 mA (depending on the distance to the base station)
Temperature:	- 30° C to + 60° C
Size:	120 x 133 x 45 mm
Protection:	IP 65

**N.L. Tucker & Associates Pty Ltd**  
**12B Pitt Way**  
**Booragoon, WA 6154**  
**P: 08 9330 7911**  
**F: 08 9317 1544**  
**sales@nltucker.com.au**

**N.L. Tucker & Associates Pty Ltd**  
**50 Marni Street**  
**Dandenong South, Victoria 3175**  
**P: 03 9706 6691**  
**F: 03 9706 6692**  
**vicsales@nltucker.com.au**