

COUGAR



Multicode Receiver T60-Cougar RX2-A	
Article number:	T60RX-03xGL
Application areas:	Doors, gates, barriers, elevators, a.o.
Frequency:	433,92 MHz
Mod.Type:	FSK
Coding:	Digital pulse code, 500 erasable codes (number of TX (codes) / RX)
Code comb.:	Unique codes; 16.777.216 (System 460: 6.561
Relay output:	3 relay outputs All functions are momentary. Function 1 and 3 are interlocked, function 2 has priority over function 1 and 3.
Radio type:	Double superheterodyne
Sensitivity:	- 100 dBm or better at 12 dB Sinad
Antenna:	External
Power supply:	12 - 24V AC / DC, 230V AC, 48V AC, 115V AC
Power consumption:	12V DC; 50-300 mA 24V DC; 25-150 mA 24V AC; 20-120 mA 230V AC; 10-25 mA 48V AC: 48-120 mA 115V AC; 20-50 mA
Temperature:	- 30° C to +70° C
Dimensions:	120 x 133 x 46 mm
Protection:	IP 65
Recommended transmitter:	All transmitter system T60-Cougar and T20 (fully compatible with system 460)

N.L. Tucker & Associates Pty Ltd
12B Pitt Way
Booragoon, WA 6154
P: 08 9330 7911
F: 08 9317 1544
sales@nltucker.com.au

N.L. Tucker & Associates Pty Ltd
50 Marni Street
Dandenong South, Victoria 3175
P: 03 9706 6691
F: 03 9706 6692
vicsales@nltucker.com.au