

# COUGAR



TX1-C



TX1-E



TX1-F

T60-Cougar transmitter TX1-x	
Application areas:	Winches, pumps, crushers, lighting, conveyor belts, hydraulics a.o.
Frequency:	433,92 MHz and 869,85 MHz
Mod.Type:	FSK
Coding:	Digital pulse code
Code comb.:	<b>433,92 MHz:</b> Adjustable codes; 59.049 (System 460: 6.561) Unique codes; 16.777.216 <b>869,85 MHz:</b> Unique codes; 16.777.216
Functions:	1, 2, 3, 4, 6 or 8
Output:	7 mW (by 50 ohm)
Antenna:	Built-in
Power supply:	3 Exchangeable 1,5V batteries type:AAA (battery change once a year with normal use)
Power consumption:	Apr. 20 mA
Temperature:	-20° C to +55° C
Weight:	Apr. 120 g incl. batteries
Dimensions:	113 x 66 x 35 mm (with clip)
Protection:	IP 65
Recommended receiver:	<b>433,92 MHz:</b> all receivers system T60-Cougar with 433,92 MHz (fully compatible with system 460). <b>869,85 MHz:</b> all receivers system T60-Cougar with 869,85 MHz

**N.L. Tucker & Associates Pty Ltd**  
12B Pitt Way  
Booragoon, WA 6154  
P: 08 9330 7911  
F: 08 9317 1544  
sales@nltucker.com.au

**N.L. Tucker & Associates Pty Ltd**  
50 Marni Street  
Dandenong South, Victoria 3175  
P: 03 9706 6691  
F: 03 9706 6692  
vicsales@nltucker.com.au