

COUGAR



TX3-A

T60-Cougar transmitter TX3-x	
Article number:	T60TX-0xxRL
Application areas:	Doors, entrances, gates, winches, pumps, crushers, lighting, telfers, conveyor belts, hydraulics a.o.
Frequency:	433,92 MHz
Mod.Type:	FSK
Coding:	Digital pulse code
Code comb.:	Adjustable codes; 59.049 (System 460: 6.561) Unique codes: 16.777.216
Functions:	8
Output:	10 mW (by 50 ohm)
Antenna:	Built-in
Power supply:	T60TX-0xSRL: 9V exchangeable battery type: 6F22 (battery change once a year with normal use). T60TX-0xCRL: Rechargeable battery T60TX-0xERL: Rechargeable battery incl. stop button
Power consumption:	Apr. 25 mA
Charging voltage:	12-30V DC
Operating time:	Rechargeable battery; 25 hrs. continuous use
Temperature:	- 20° C to +55° C
Weight:	Apr. 250 g incl. battery
Dimensions:	160 x 70 x 35 mm
Protection:	IP 54
Recommended receiver:	T60-Cougar receiver RX1-A and RX3-A with 4 or 8 relays (fully compatible with system 460).

N.L. Tucker & Associates Pty Ltd
12B Pitt Way
Booragoon, WA 6154
P: 08 9330 7911
F: 08 9317 1544
sales@nltucker.com.au

N.L. Tucker & Associates Pty Ltd
50 Marni Street
Dandenong South, Victoria 3175
P: 03 9706 6691
F: 03 9706 6692
vicsales@nltucker.com.au