

# COUGAR



TX4-A

T60-Cougar transmitter TX4-x	
Article number:	T60TX-04xDL
Application areas:	Doors, entrances, gates, winches, pumps, crushers, lighting, conveyor belts, hydraulics, a.o.
Frequency:	433,92 MHz
Mod. Type:	FSK
Coding:	Digital pulse cod
Code comb.:	Adjustable codes; 59.049 (System 460: 6.561) Unique codes; 16.777.216
Functions:	2 x 4
Output:	10 mW (by 50 ohm)
Antenna:	Built-in
Power supply:	T60TX-04SDL: 9V exchangeable battery type: 6F22 (battery change once a year with normal use). T60TX-04CDL: Rechargeable battery T60TX-04EDL: Rechargeable battery incl. stop button
Power consumption:	Apr. 25 mA
Charging voltage:	12-30V DC
Operating time:	Rechargeable battery; 25 hrs. continuous use
Temperature:	- 20° C to +55° C
Weight:	Apr. 250 g incl. battery
Dimensions:	160 x 70 x 35 mm
Protection:	IP 54
Recommended receiver:	T60-Cougar receiver RX1-A and RX3-A with 4 or 8 relays (fully compatible with system 460)

**N.L. Tucker & Associates Pty Ltd**  
**12B Pitt Way**  
**Booragoon, WA 6154**  
**P: 08 9330 7911**  
**F: 08 9317 1544**  
**sales@nltucker.com.au**

**N.L. Tucker & Associates Pty Ltd**  
**50 Marni Street**  
**Dandenong South, Victoria 3175**  
**P: 03 9706 6691**  
**F: 03 9706 6692**  
**vicsales@nltucker.com.au**