

# Jaguar



RX1

<b>T70-Jaguar receiver RX1:</b>	
Article number:	T70RX-03AIB
Application areas:	Mobile and winch applications
Frequency:	433 - 434 MHz (64 channels), 25 kHz channel spacing
Mod.Type:	Narrow band FM-modulation
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Relay output:	3, either 2 relay outputs + 1 working realy or 3 relay outputs with interlocking functions
Radio type:	Low IF receiver architecture
Sensitivity:	- 105 dBm at 1/1000 PER
Antenna:	External BNC
Power supply:	6-26 V AC / DC
Power consumption:	20 - 100 mA
Temperature:	- 20° C to +55° C
Dimensions:	120 x 133 x 45 mm (4,72 x 5,24 x 1,77 in)
Protection:	IP 65
Recommended transmitter:	T70-Jaguar TX1-x

**N.L. Tucker & Associates Pty Ltd**  
**12B Pitt Way**  
**Booragoon, WA 6154**  
**P: 08 9330 7911**  
**F: 08 9317 1544**  
**sales@nltucker.com.au**

**N.L. Tucker & Associates Pty Ltd**  
**50 Marni Street**  
**Dandenong South, Victoria 3175**  
**P: 03 9706 6691**  
**F: 03 9706 6692**  
**vicsales@nltucker.com.au**