

# Jaguar



TXI-A



TXI-B



TXI-C

<b>T70-Jaguar transmitter TX1-x:</b>	
Article number:	T70TX-02TTB (TXI-A), T70TX-03STB (TXI-B), T70TX-06TTB (TXI-C)
Application areas:	Mobile and winch applications
Frequency:	433 - 434 MHz (64 channels), 25 kHz channel spacing
Mod. Type:	Narrowband FM-modulation
Coding:	Digital pulse code
Code comb.:	Unique codes; 16.777.216
Functions:	TXI-A; 2 functions + ON/OFF TXI-B; 3 functions + ON/OFF TXI-C; 6 functions + ON/OFF
Output:	10 mW (by 50 ohm)
Antenna:	Built-in
Power supply:	3 Exchangeable 1,5V batteries type:AAA (battery change once a year with normal use)
Power consumption:	Apr. 20 mA
Temperature:	-20° C to +55° C
Weight:	Apr. 120 g incl. batteries
Dimensions:	113 x 66 x 35 mm (including clip)
Protection:	IP 65
Recommended receiver:	T70-Jaguar RXI

**N.L. Tucker & Associates Pty Ltd**  
**12B Pitt Way**  
**Booragoon, WA 6154**  
**P: 08 9330 7911**  
**F: 08 9317 1544**  
**sales@nltucker.com.au**

**N.L. Tucker & Associates Pty Ltd**  
**50 Marni Street**  
**Dandenong South, Victoria 3175**  
**P: 03 9706 6691**  
**F: 03 9706 6692**  
**vicsales@nltucker.com.au**