



T20RX-03ASL



T20TX-03EWS

Winch kit T20-03EWS/RWS:	
Contents T20-03EWS/RWS:	Transmitter T20TX-03EWS, receiver T20RX-03ASL and external antenna. T20-03EWS incl. cables and T20-RWS excl. cables.
Area of application:	Electric and hydraulic winches
Frequency:	433.92 MHz
Mod.Type:	FSK
Coding:	Digital pulse code
Code combinations:	Individual codes 16,777,216 (optional)
Relay output:	2 (3) relay outputs: saves 30 codes
Radio type:	Double superheterodyne
Sensitivity:	- 104 dBm or better a 12 dB Sinad
Antenna RX:	External
Operating voltage:	RX: 12 - 24 V AC/DC TX: 3 x 1.5V batteries type AAA
Power consumption RX:	12 V DC; 50-300 mA 24 V DC; 25-150 mA 24 V AC; 20-120 mA
Power consumption TX:	20 mA
Temperature:	RX: -30° to +70° C (-22° to 158° F) TX: -20° to +55° C (-4° to 131° F)
Size:	RX: 120 x 133 x 45 mm (4.72 X 5.24 X 1.77 inch) TX: 113 x 66 x 35 mm (4.45 x 2.6 x 1.38 inch)
Protection:	RX: IP 65 TX: IP 65

<p>Australian Distributors: N.L. Tucker & Assoc. 12B Pitt Way BOORAGOON WA 6154 Ph: (08) 9330 7911 Fax: (08) 9317 1544 Email: sales@nltucker.com.au Web: www.nltucker.com.au</p>	<p>N.L. Tucker & Assoc 50 Marni Street DANDENONG SOUTH VIC 3175 Ph: (03) 9706 6691 Fax: (03) 9706 6692 Email: vicsales@nltucker.com.au Web: www.nltucker.com.au</p>
---	---