



T60RX-04*SL/*SM

Receiver T60RX-04*SL/*SM	
Article no.	T60RX-04*SL/*SM
Frequency	433 & 869 MHz , 1 channels
No. of function relays	4
Duplex	No
Power supply	12-24V DC & 230V AC & 115V AC & 24V AC
Max current consumption	10-300 mA
Dimensions	~ 133 x 120 x 45 mm / ~ 5.2 x 4.7 x 1.8 in
Protection	IP65
Radio type	Double superheterodyne
Sensitivity	-100 dBm
Bus system	None
Relay functionality	Momentary, Latching, Interlocking
Antenna	1 external BNC
Temperature	-20 to +55 C / -4 to +130 F
869 MHz:	ASM= 12-24V AC, BSM= 230V AC
Max. number of transmitters	40

The product picture above is for illustrative purposes only, actual product appearance might be slightly different.

N.L. Tucker & Assoc.
12B Pitt Way
BOORAGOON WA
6154
Ph: (08) 9330 7911
Fax: (08) 9317 1544
Email: sales@nltucker.com.au
Web: www.nltucker.com.au

N.L. Tucker & Assoc
50 Marni Street
DANDENONG SOUTH VIC
3175
Ph: (03) 9706 6691
Fax: (03) 9706 6692
Email: vicsales@nltucker.com.au
Web: www.nltucker.com.au