



## Type EW-PP



Cable protection conduit closed

### PRODUCT INFORMATION






The self-extinguishing EW-PP cable protection conduits are made of specially modified polypropylene. The material is phosphor and cadmium-free. The EW-PP cable protection conduits are characterised by outstanding chemical resistance, good crush and impact resistance.

For static and dynamic applications involving medium to high mechanical loads.

Applications:

- Plant engineering
- Mechanical engineering
- Chemical plants

### SPECIFICATIONS

-  Mod. Polypropylene
-  In conformity with IEC EN 61386 > 70 N/100 mm
-  > 3100000 ~ In conformity with IEC EN 61386
-  -40 – 130 °C transient / short term  
150 °C
-  V2 self-extinguishing

RoHS


Made in Germany

Type	Order No.	Colour	A Ø mm	B Ø mm	R stat. mm	R dyn. mm	Weight kg/100m	Pack m
<b>Standard corrugation</b>								
EW-PP-M10/P7	83201050	Black	8.20	11.50	21.00	70.00	1.30	50
EW-PP-M12/P9	83201052	Black	9.60	12.80	26.00	80.00	2.40	50
EW-PP-M16/P11	83201054	Black	11.90	15.70	33.00	100.00	3.50	50
EW-PP-M20/P16	83201056	Black	15.60	21.00	46.00	180.00	5.20	50
EW-PP-M25/P21	83201058	Black	22.50	28.30	59.00	230.00	9.30	50
EW-PP-M32/P29	83201060	Black	27.80	34.30	72.00	280.00	11.00	25
EW-PP-M40/P36	83201062	Black	34.70	42.20	86.00	310.00	16.00	25
EW-PP-M50/P48	83201064	Black	46.70	54.00	107.00	350.00	21.00	25
EW-PP-70 Jumbo	83201066	Black	67.80	79.80	160.00	600.00	41.00	25
EW-PP-95 Jumbo	83201068	Black	89.60	106.30	200.00	800.00	75.00	10
<b>Grey</b>								
EW-PP-M10/P7	83201010	Grey	8.20	11.50	21.00	70.00	1.30	50
EW-PP-M12/P9	83201012	Grey	9.60	12.80	26.00	80.00	2.40	50
EW-PP-M16/P11	83201014	Grey	11.90	15.70	33.00	100.00	3.50	50
EW-PP-M20/P16	83201016	Grey	15.60	21.00	46.00	180.00	5.20	50
EW-PP-M25/P21	83201018	Grey	21.60	28.30	59.00	230.00	9.30	50
EW-PP-M32/P29	83201020	Grey	27.80	34.30	72.00	280.00	11.00	25
EW-PP-M40/P36	83201022	Grey	34.70	42.20	86.00	310.00	16.00	25
EW-PP-M50/P48	83201024	Grey	46.70	54.00	107.00	350.00	21.00	25
EW-PP-70 Jumbo	83201026	Grey	67.80	79.80	160.00	600.00	41.00	25
EW-PP-95 Jumbo	83201028	Grey	89.60	106.30	200.00	800.00	75.00	10

## Type EW-PP

Type	Order No.	Colour	A Ø mm	B Ø mm	R stat. mm	R dyn. mm	Weight kg/100m	Pack m
<b>Narrow corrugation</b>								
EW-PP-M20/P16S	83201057	Black	16.40	20.90	41.00	170.00	5.10	50

### MATERIAL PROPERTIES

 Mod. Polypropylene

### MECHANICAL PROPERTIES

 **Crush resistance**  
Crush resistance: > 700 N/100 mm; Testing method: In conformity with IEC EN 61386; Note: EW-PP-M25/P21

 **Flexural fatigue strength**  
Cycles: > 3100000 ~; Testing method: In conformity with IEC EN 61386; Test value: M25/P21

### THERMAL PROPERTIES

 **Temperature / temperature range**  
-40 – 130 °C transient / short term 150 °C

### FIRE BEHAVIOUR

 **Fire classification**  
V2 self-extinguishing

### CONFORMITY

 **RoHS (EC Directive 2002/95/EC)**

### GENERAL INFORMATION

 **Made in Germany**

All details given in our sales material prospectuses and catalogues as well as the information available online are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

This does not free the purchaser of carrying out their own inspections and tests in order to determine the suitability of a product for a specific purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.

© Murrplastik Systemtechnik GmbH • proID\_64170~20161025~890283~suv\_ew\_pp