



T20RX-03ASL



T20TX-03EWS

Winch kit T20-03EWS/RWS:	
Contents T20-03EWS/RWS:	Transmitter T20TX-03EWS, receiver T20RX-03ASL and external antenna. T20-03EWS incl. cables and T20-RWS excl. cables.
Area of application:	Electric and hydraulic winches
Frequency:	433.92 MHz
Mod.Type:	FSK
Coding:	Digital pulse code
Code combinations:	Individual codes 16,777,216 (optional)
Relay output:	2 (3) relay outputs: saves 30 codes
Radio type:	Double superheterodyne
Sensitivity:	- 104 dBm or better a 12 dB Sinad
Antenna RX:	External
Operating voltage:	RX: 12 - 24 V AC/DC TX: 3 x 1.5V batteries type AAA
Power consumption RX:	12 V DC; 50-300 mA 24 V DC; 25-150 mA 24 V AC; 20-120 mA
Power consumption TX:	20 mA
Temperature:	RX: -30° to +70° C (-22° to 158° F) TX: -20° to +55° C (-4° to 131° F)
Size:	RX: 120 x 133 x 45 mm (4.72 X 5.24 X 1.77 inch) TX: 113 x 66 x 35 mm (4.45 x 2.6 x 1.38 inch)
Protection:	RX: IP 65 TX: IP 65

N.L. Tucker & Assoc.
12B Pitt Way
BOORAGOON WA
6154
Ph: (08) 9330 7911
Fax: (08) 9317 1544
Email: sales@nltucker.com.au
Web: www.nltucker.com.au

N.L. Tucker & Assoc
50 Marni Street
DANDENONG SOUTH VIC
3175
Ph: (03) 9706 6691
Fax: (03) 9706 6692
Email: vicsales@nltucker.com.au
Web: www.nltucker.com.au